


REV	DATE	DESCRIPTION	ECO	SIGN
1	2/15/01	RELEASE TO PILOT	1013	RAB
2	8/15/01	Change Male Thread Length to 1"	1069	RAB
3	8/7/02	Chg. M.E. , Rec. & Male Thrd Lg to 1.5"	1143	RAB

3/4-16 UNF 2A BOTH ENDS.



1"Wx1/2"Lg.
WRENCH FLATS

TURK RECEPTACLE
MALE WITH EX.THDS. FS 4.5/18.25

4M LOAD CELL CABLE. P.N. 4245-222

SPECIFICATIONS:

RATED CAPACITY	10,000 POUNDS
RATED OUTPUT	2mV/V
COMBINED ERROR	0.25% OF F.S.
NON-REPEATABILITY	0.05%
ZERO BALANCE	1%
TEMPERATURE RANGE, COMPENSATED	14 to 104°F
TEMPERATURE EFFECT, OUTPUT	0.018%/°F
TEMPERATURE EFFECT, ZERO BALANCE	0.005%/°F
INPUT IMPEDANCE, (typical)	350 OHMS
EXCITATION VOLTAGE (typical)	10VDC or VAC rms
EXCITATION VOLTAGE, MAXIMUM	15VDC or VAC rms
INSULATION RESISTANCE	5,000 MEG.OHMS @ 50 VDC
MAXIMUM LOAD, SAFE	150% F.S.
MAXIMUM LOAD, ULTIMATE	200% F.S.
NORMAL INSTALLATION TORQUE: 120 FT-LBS. 240 FT-LBS OR MORE WILL RESULT IN UN-REPAIRABLE DAMAGE.	


WIRE COLOR CODE:

PIN NO.

+EXCITATION	BROWN	1
+SIGNAL	WHITE	2
-SIGNAL	BLUE	3
-EXCITATION	BLACK	4

TURK FS 4.5/18.25 or EQ.

(RECEPTACLE FRONT SIDE)



TOLERANCES UNLESS OTHERWISE SPECIFIED:

.XXX=0.005
.XX=0.015
.X=0.025

SCALE: FULL

FINISH: BRUSHED STAINLESS COVER

LOAD CELL MAT'L: ALLOY STEEL



TOLEDO
TRANSDUCERS,
INC.

Designed By: Mettert

Date: 1/18/99

Drawn By:

Date:

Approved By:

Date:

Title / Description:

SS1239 10,000 POUND
UNIVERSAL LOAD CELL

Dwg. Size:

A

Dwg. Type:

SPEC

Page 1 of 1

Part No.

SS1239-10K

File Name

11168SP.FCD

Doc. No.

11168